

Safety Data Sheet

Copyright, 2018, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

 Document Group:
 19-2499-2
 Version Number:
 9.04

 Issue Date:
 07/26/18
 Supercedes Date:
 06/18/18

SECTION 1: Identification

1.1. Product identifier

3M Fire Barrier Watertight Sealant 3000 WT

Product Identification Numbers

ID Number UPC ID Number UPC

 98-0400-5503-4
 000-51115-16593-1
 98-0400-5504-2
 500-51115-16594-3

 98-0400-5553-9
 000-51115-18788-9
 98-0400-5586-9
 000-51115-18797-1

7000006386, 7100006306, 7000059413

1.2. Recommended use and restrictions on use

Recommended use

Caulk, Fire barrier caulking.

1.3. Supplier's details

MANUFACTURER: 3M

DIVISION: Industrial Adhesives and Tapes Division **ADDRESS:** 3M Center, St. Paul, MN 55144-1000, USA

Telephone. 1,888,2M HELDS (1,888,264,2577)

Telephone: 1-888-3M HELPS (1-888-364-3577)

1.4. Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

SECTION 2: Hazard identification

2.1. Hazard classification

Serious Eye Damage/Irritation: Category 2A.

Skin Corrosion/Irritation: Category 2.

Skin Sensitizer: Category 1B.

Carcinogenicity: Category 1B.

Specific Target Organ Toxicity (single exposure): Category 1. Specific Target Organ Toxicity (repeated exposure): Category 1.

2.2. Label elements

Signal word

Page 1 of 12

Danger

Symbols

Exclamation mark | Health Hazard |

Pictograms





Hazard Statements

Causes serious eye irritation.

Causes skin irritation.

May cause an allergic skin reaction.

May cause cancer.

Causes damage to organs:

blood or blood-forming organs

Causes damage to organs through prolonged or repeated exposure:

blood or blood-forming organs

May cause damage to organs through prolonged or repeated exposure:

kidney/urinary tract

Precautionary Statements

General:

Keep out of reach of children.

Prevention:

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Do not breathe dust/fume/gas/mist/vapors/spray.

Wear protective gloves and eye/face protection.

Do not eat, drink or smoke when using this product.

Wash thoroughly after handling.

Contaminated work clothing must not be allowed out of the workplace.

Response:

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

If eye irritation persists: Get medical advice/attention.

IF ON SKIN: Wash with plenty of soap and water.

If skin irritation or rash occurs: Get medical advice/attention.

Take off contaminated clothing and wash it before reuse.

IF exposed or concerned: Get medical advice/attention.

Storage:

Store locked up.

Disposal:

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

Page 2 of 12

SECTION 3: Composition/information on ingredients

| Ingredient | C.A.S. No. | % by Wt |
|---|-------------|--------------------------|
| Melamine | 108-78-1 | 30 - 60 Trade Secret * |
| Siloxanes and Silicones, Di-Me, Hydroxy-Terminated | 70131-67-8 | 15 - 40 Trade Secret * |
| Graphite | 7782-42-5 | 10 - 30 Trade Secret * |
| Poly(Dimethylsiloxane) | 63148-62-9 | 10 - 30 Trade Secret * |
| Methyl Tris(Butylideneaminooxy)Silane | 22984-54-9 | 3 - 7 Trade Secret * |
| Silica | 7631-86-9 | 0 - 5 Trade Secret * |
| Synthetic Amorphous Silica, Fumed, Crystalline Free | 112945-52-5 | 0 - 5 Trade Secret * |
| (3-Aminopropyl)Triethoxysilane | 919-30-2 | 0.5 - 1.5 Trade Secret * |
| 3-Iodo-2-Propynyl Butylcarbamate | 55406-53-6 | < 0.1 Trade Secret * |

^{*}The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Remove person to fresh air. If you feel unwell, get medical attention.

Skin Contact:

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye Contact:

Immediately flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. Get medical attention.

If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1. Information on toxicological effects.

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

Material will not burn. Use a fire fighting agent suitable for the surrounding fire.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

5.3. Special protective actions for fire-fighters

No special protective actions for fire-fighters are anticipated.

SECTION 6: Accidental release measures

12

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid breathing of vapors created during cure cycle. Keep out of reach of children. Do not handle until all safety precautions have been read and understood. Do not breathe dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.) Use personal protective equipment (gloves, respirators, etc.) as required.

7.2. Conditions for safe storage including any incompatibilities

Store away from oxidizing agents.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

| Ingredient | C.A.S. No. | Agency | Limit type | Additional Comments |
|--------------------|------------|--------|-------------------------------|----------------------------|
| Melamine | 108-78-1 | AIHA | TWA(inhalable particulates):3 | |
| | | | mg/m3 | |
| SILICA, AMORPHOUS | 112945-52- | OSHA | TWA concentration:0.8 | |
| | 5 | | mg/m3;TWA:20 millions of | |
| | | | particles/cu. ft. | |
| SILICA, AMORPHOUS | 7631-86-9 | OSHA | TWA concentration:0.8 | |
| | | | mg/m3;TWA:20 millions of | |
| | | | particles/cu. ft. | |
| Graphite | 7782-42-5 | ACGIH | TWA(respirable fraction):2 | |
| | | | mg/m3 | |
| Graphite | 7782-42-5 | OSHA | TWA:15 millions of | |
| _ | | | particles/cu. ft. | |
| GRAPHITE SYNTHETIC | 7782-42-5 | OSHA | TWA(as total dust):15 | |
| | | | mg/m3;TWA(respirable | |
| | | | fraction):5 mg/m3 | |

ACGIH: American Conference of Governmental Industrial Hygienists

AIHA: American Industrial Hygiene Association

CMRG: Chemical Manufacturer's Recommended Guidelines

OSHA: United States Department of Labor - Occupational Safety and Health Administration

TWA: Time-Weighted-Average STEL: Short Term Exposure Limit

CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Provide ventilated enclosure for heat curing. Curing enclosures must be exhausted to outdoors or to a suitable emission control device. Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Indirect Vented Goggles

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity. Gloves made from the following material(s) are recommended: Polymer laminate

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron - polymer laminate

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapors and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

General Physical Form:Solid **Specific Physical Form:**Paste

Odor, Color, Grade:
Light gray with black flecks, thixotropic paste
No Data Available

No Data Available pН Not Applicable Melting point Not Applicable **Boiling Point** No Data Available **Flash Point** No flash point **Evaporation rate** No Data Available Flammability (solid, gas) Not Classified Flammable Limits(LEL) No Data Available Flammable Limits(UEL) No Data Available

Vapor Pressure Nil Vapor Density Nil

Specific Gravity 1.25 [Ref Std:WATER=1]

Page 5 of 12

3M Fire Barrier Watertight Sealant 3000 WT

07/26/18

Solubility in Water Nil

Solubility- non-waterNo Data AvailablePartition coefficient: n-octanol/ waterNo Data AvailableAutoignition temperatureNot ApplicableDecomposition temperatureNo Data AvailableViscosityNo Data AvailableMolecular weightNo Data Available

Volatile Organic Compounds <=5.3 % weight [*Test Method:*tested per EPA method 24]

Percent volatile No Data Available

VOC Less H2O & Exempt Solvents <=65 g/l [*Test Method:*tested per EPA method 24]

SECTION 10: Stability and reactivity

10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

Not determined

10.5. Incompatible materials

Strong oxidizing agents

10.6. Hazardous decomposition products

SubstanceConditionFormaldehydeNot SpecifiedCarbon monoxideNot SpecifiedCarbon dioxideNot SpecifiedOxides of NitrogenNot Specified

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

Page 6 of 12

May cause additional health effects (see below).

Skin Contact:

Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, dryness, cracking, blistering, and pain. Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Eye Contact:

Severe Eye Irritation: Signs/symptoms may include significant redness, swelling, pain, tearing, cloudy appearance of the cornea, and impaired vision.

Ingestion:

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

May cause additional health effects (see below).

Additional Health Effects:

Single exposure may cause target organ effects:

Blood Effects: Signs/symptoms may include generalized weakness and fatigue, skin pallor, changes in blood clotting time, internal bleeding, and/or hemoglobinemia.

Prolonged or repeated exposure may cause target organ effects:

Blood Effects: Signs/symptoms may include generalized weakness and fatigue, skin pallor, changes in blood clotting time, internal bleeding, and/or hemoglobinemia.

Kidney/Bladder Effects: Signs/symptoms may include changes in urine production, abdominal or lower back pain, increased protein in urine, increased blood urea nitrogen (BUN), blood in urine, and painful urination.

Carcinogenicity:

Contains a chemical or chemicals which can cause cancer.

| Ingredient | CAS No. | Class Description | Regulation |
|------------|----------|-------------------------------|---|
| Melamine | 108-78-1 | Grp. 2B: Possible human carc. | International Agency for Research on Cancer |

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

| Name | Route | Species | Value |
|---|--------------------------|---------|--|
| Overall product | Dermal | | No data available; calculated ATE >5,000 mg/kg |
| Overall product | Ingestion | | No data available; calculated ATE >5,000 mg/kg |
| Melamine | Dermal | Rabbit | LD50 > 1,000 mg/kg |
| Melamine | Ingestion | Rat | LD50 3,161 mg/kg |
| Siloxanes and Silicones, Di-Me, Hydroxy-Terminated | Dermal | Rabbit | LD50 > 16,000 mg/kg |
| Siloxanes and Silicones, Di-Me, Hydroxy-Terminated | Ingestion | Rat | LD50 > 64,000 mg/kg |
| Graphite | Dermal | | LD50 estimated to be > 5,000 mg/kg |
| Poly(Dimethylsiloxane) | Dermal | Rabbit | LD50 > 19,400 mg/kg |
| Graphite | Ingestion | Rat | LD50 > 2,000 mg/kg |
| Poly(Dimethylsiloxane) | Ingestion | Rat | LD50 > 17,000 mg/kg |
| Methyl Tris(Butylideneaminooxy)Silane | Dermal | | LD50 estimated to be 2,000 - 5,000 mg/kg |
| Methyl Tris(Butylideneaminooxy)Silane | Ingestion | Rat | LD50 2,260 mg/kg |
| Silica | Dermal | Rabbit | LD50 > 5,000 mg/kg |
| Synthetic Amorphous Silica, Fumed, Crystalline Free | Dermal | Rabbit | LD50 > 5,000 mg/kg |
| Silica | Inhalation- Dust/Mist | Rat | LC50 > 0.691 mg/l |

Page 7 of 12

07/26/18

| | (4 hours) | | |
|---|-------------|--------|--------------------|
| Silica | Ingestion | Rat | LD50 > 5,110 mg/kg |
| Synthetic Amorphous Silica, Fumed, Crystalline Free | Inhalation- | Rat | LC50 > 0.691 mg/l |
| | Dust/Mist | | |
| | (4 hours) | | |
| Synthetic Amorphous Silica, Fumed, Crystalline Free | Ingestion | Rat | LD50 > 5,110 mg/kg |
| (3-Aminopropyl)Triethoxysilane | Dermal | Rabbit | LD50 4,290 mg/kg |
| (3-Aminopropyl)Triethoxysilane | Ingestion | Rat | LD50 1,570 mg/kg |
| 3-Iodo-2-Propynyl Butylcarbamate | Dermal | Rabbit | LD50 > 2,000 mg/kg |
| 3-Iodo-2-Propynyl Butylcarbamate | Inhalation- | Rat | LC50 0.67 mg/l |
| | Dust/Mist | | |
| | (4 hours) | | |
| 3-Iodo-2-Propynyl Butylcarbamate | Ingestion | Rat | LD50 1,056 mg/kg |

ATE = acute toxicity estimate

Skin Corrosion/Irritation

| Name | Species | Value |
|---|---------|---------------------------|
| | | |
| Melamine | Guinea | No significant irritation |
| | pig | |
| Graphite | Rabbit | No significant irritation |
| Poly(Dimethylsiloxane) | Rabbit | No significant irritation |
| Silica | Rabbit | No significant irritation |
| Synthetic Amorphous Silica, Fumed, Crystalline Free | Rabbit | No significant irritation |
| (3-Aminopropyl)Triethoxysilane | Rabbit | Corrosive |
| 3-Iodo-2-Propynyl Butylcarbamate | Rabbit | Minimal irritation |

Serious Eye Damage/Irritation

| Name | Species | Value |
|---|---------|---------------------------|
| | | |
| Melamine | Rabbit | No significant irritation |
| Graphite | Rabbit | No significant irritation |
| Poly(Dimethylsiloxane) | Rabbit | No significant irritation |
| Silica | Rabbit | No significant irritation |
| Synthetic Amorphous Silica, Fumed, Crystalline Free | Rabbit | No significant irritation |
| (3-Aminopropyl)Triethoxysilane | Rabbit | Corrosive |
| 3-Iodo-2-Propynyl Butylcarbamate | Rabbit | Corrosive |

Skin Sensitization

| Name | Species | Value |
|---|----------|----------------|
| Melamine | Guinea | Not classified |
| | pig | |
| Silica | Human | Not classified |
| | and | |
| | animal | |
| Synthetic Amorphous Silica, Fumed, Crystalline Free | Human | Not classified |
| | and | |
| | animal | |
| (3-Aminopropyl)Triethoxysilane | Guinea | Sensitizing |
| | pig | |
| 3-Iodo-2-Propynyl Butylcarbamate | Multiple | Sensitizing |
| | animal | |
| | species | |

Respiratory Sensitization

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

| our in our management, | | | |
|------------------------|----------|---------------|--|
| Name | Route | Value | |
| Melamine | In Vitro | Not mutagenic | |
| Melamine | In vivo | Not mutagenic | |

| 3M I | ire Barrier | Watertight Sealant 3000 WT | 07/26/18 |
|------|-------------|----------------------------|----------|
|------|-------------|----------------------------|----------|

| Siloxanes and Silicones, Di-Me, Hydroxy-Terminated | In Vitro | Not mutagenic |
|---|----------|--|
| Graphite | In Vitro | Some positive data exist, but the data are not |
| | | sufficient for classification |
| Silica | In Vitro | Not mutagenic |
| Synthetic Amorphous Silica, Fumed, Crystalline Free | In Vitro | Not mutagenic |

Carcinogenicity

| Name | Route | Species | Value |
|---|-----------|----------|--|
| Melamine | Ingestion | Multiple | Carcinogenic |
| | | animal | |
| | | species | |
| Silica | Not | Mouse | Some positive data exist, but the data are not |
| | Specified | | sufficient for classification |
| Synthetic Amorphous Silica, Fumed, Crystalline Free | Not | Mouse | Some positive data exist, but the data are not |
| | Specified | | sufficient for classification |

Reproductive Toxicity

Reproductive and/or Developmental Effects

| Name | Route | Value | Species | Test Result | Exposure Duration |
|--|-----------|--|---------|--------------------------|-----------------------------|
| Melamine | Ingestion | Not classified for development | Rat | NOAEL 1,060 mg/kg/day | during organogenesi s |
| Silica | Ingestion | Not classified for female reproduction | Rat | NOAEL 509 mg/kg/day | 1 generation |
| Silica | Ingestion | Not classified for male reproduction | Rat | NOAEL 497 mg/kg/day | 1 generation |
| Silica | Ingestion | Not classified for development | Rat | NOAEL 1,350 mg/kg/day | during organogenesi s |
| Synthetic Amorphous Silica, Fumed, Crystalline Free | Ingestion | Not classified for female reproduction | Rat | NOAEL 509 mg/kg/day | 1 generation |
| Synthetic Amorphous Silica, Fumed, Crystalline Free | Ingestion | Not classified for male reproduction | Rat | NOAEL 497 mg/kg/day | 1 generation |
| Synthetic Amorphous Silica, Fumed, Crystalline Free | Ingestion | Not classified for development | Rat | NOAEL 1,350 mg/kg/day | during organogenesi s |

Target Organ(s)

Specific Target Organ Toxicity - single exposure

For the component/components, either no data are currently available or the data are not sufficient for classification.

Specific Target Organ Toxicity - repeated exposure

| Name | Route | Target Organ(s) | Value | Species | Test Result | Exposure Duration |
|---|------------|-----------------------------------|--|---------|------------------------|-----------------------|
| Melamine | Ingestion | kidney and/or bladder | May cause damage to organs though prolonged or repeated exposure | Rat | LOAEL 63 mg/kg/day | 13 weeks |
| Graphite | Inhalation | pneumoconiosis | Not classified | Human | NOAEL Not available | occupational exposure |
| Silica | Inhalation | respiratory system silicosis | Not classified | Human | NOAEL Not available | occupational exposure |
| Synthetic Amorphous Silica, Fumed, Crystalline Free | Inhalation | respiratory system silicosis | Not classified | Human | NOAEL Not available | occupational exposure |
| 3-Iodo-2-Propynyl Butylcarbamate | Inhalation | respiratory system | Causes damage to organs through prolonged or repeated exposure | Rat | NOAEL 0.00116 mg/l | 90 days |

Aspiration Hazard

For the component/components, either no data are currently available or the data are not sufficient for classification.

Page 9 of 12 Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

Ecotoxicological information

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

Chemical fate information

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

SECTION 13: Disposal considerations

13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of waste product in a permitted industrial waste facility. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

EPA Hazardous Waste Number (RCRA): Not regulated

SECTION 14: Transport Information

For Transport Information, please visit http://3M.com/Transportinfo or call 1-800-364-3577 or 651-737-6501

SECTION 15: Regulatory information

15.1. US Federal Regulations

Contact 3M for more information.

EPCRA 311/312 Hazard Classifications:

Physical Hazards

Not applicable

Health Hazards

Carcinogenicity

Respiratory or Skin Sensitization

Serious eye damage or eye irritation

Skin Corrosion or Irritation

Specific target organ toxicity (single or repeated exposure)

15.2. State Regulations

Contact 3M for more information.

15.3. Chemical Inventories

07/26/18

The components of this material are in compliance with the provisions of Australia National Industrial Chemical Notification and Assessment Scheme (NICNAS). Certain restrictions may apply. Contact the selling division for additional information.

The components of this product are in compliance with the new substance notification requirements of CEPA.

The components of this material are in compliance with the China "Measures on Environmental Management of New Chemical Substance". Certain restrictions may apply. Contact the selling division for additional information.

The components of this material are in compliance with the provisions of the Korean Toxic Chemical Control Law. Certain restrictions may apply. Contact the selling division for additional information.

The components of this material are in compliance with the provisions of Philippines RA 6969 requirements. Certain restrictions may apply. Contact the selling division for additional information.

The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

Contact 3M for more information.

15.4. International Regulations

Contact 3M for more information.

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SECTION 16: Other information

NFPA Hazard Classification

Health: 2 Flammability: 0 Instability: 0 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

HMIS Hazard Classification

Health: *2 Flammability: 0 Physical Hazard: 0 Personal Protection: X - See PPE section.

Hazardous Material Identification System (HMIS® IV) hazard ratings are designed to inform employees of chemical hazards in the workplace. These ratings are based on the inherent properties of the material under expected conditions of normal use and are not intended for use in emergency situations. HMIS® IV ratings are to be used with a fully implemented HMIS® IV program. HMIS® is a registered mark of the American Coatings Association (ACA).

 Document Group:
 19-2499-2
 Version Number:
 9.04

 Issue Date:
 07/26/18
 Supercedes Date:
 06/18/18

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued.3MMAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3Mproduct is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3Mproduct, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3Mproduct to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3Mprovides information in electronic form as a service to its customers. Due to the remote possibility that electronic

Page 11 of 12

transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M

3M USA SDSs are available at www.3M.com

Page 12 of 12