

FOSTER 30-80 802266PM

#### SAFETY DATA SHEET

REVISION DATE: 02-11-2020 SUPERSEDES: 03-06-2017

### SECTION 1: IDENTIFICATION OF THE PRODUCT AND SUPPLIER

#### PRODUCT INFORMATION

PRODUCT: FOSTER 30-80

PRODUCT DESCRIPTION: Coating
INTENDED USE: Coating
PRODUCT IDENTIFIER: 802266PM

### **COMPANY INFORMATION**

H.B. Fuller Construction Products Inc.

1105 S. Frontenac Street Aurora, IL 60504

Phone: 1-800-552-6225

Medical Emergency Phone Number (24 Hours): 1-888-853-1758 Transport Emergency Phone Number (CHEMTREC): 1-800-424-9300

### **SECTION 2: HAZARDS IDENTIFICATION**

# **GHS Hazard Symbols:**





**GHS Signal Word:** Warning

GHS Classification: Skin Sensitisation Category 1; Hazardous to the aquatic environment - Acute Category

1; Hazardous to the aquatic environment - Chronic Category 2; Additional category for

effects on or via lactation

**GHS Hazard Phrases:** May cause an allergic skin reaction.; May cause harmto breast-fed children.; Very

toxic to aquatic life.; Toxic to aquatic life with long lasting effects.

**GHS Precautions:** 

**Safety Precautions:** Obtain special instructions before use. Do not breathe

dust/fume/gas/mist/vapours/spray. Avoid contact during pregnancy/while nursing. Wash thoroughly after handling. Do no eat, drink or smoke when using this product. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wear protective gloves/protective clothing/eye protection/face

protection.

**First Aid Measures:** IF ON SKIN: Wash with plenty of soap and water.

**Disposal:** Dispose of contents/container in accordance with local/regional/national/international

regulation for chemical wastes.

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS #	PERCENT	Classification	Note
Chlorinated paraffin, C14-C17	61788-76-9	5 - 10	Aquatic Acute 1; H400	
			Aquatic Chronic 1; H410	
Hindered amine light stabilizer	41556-26-7	0.1 - 1	Aquatic Acute 1; H400	
			Aquatic Chronic 1; H410	
			Skin Sens. 1; H317	



FOSTER 30-80 802266PM

#### SAFETY DATA SHEET

Tri(nonylphenol)phosphite	26523-78-4	0.1 - 1	Aquatic Chronic 1; H410	
			Skin Sens. 1; H317	
Decanedioic acid, methyl 1,2,2,6,6-	82919-37-7	0.1 - 1	Aquatic Chronic 2; H411	
pentamethyl-4-piperidinyl ester			Skin Sens. 1; H317	

\*This product contains one or more materials that may be hazardous when present as an airborne dust. During normal handling of the product, the material is encapsulated within the product and will not present an exposure risk. Once the product has reached its final state and is abraded or disturbed, dusting and exposure may occur. This product contains titanium dioxide, which is hazardous when present as an airborne dust. As provided, and during normal use of this product, this substance is encapsulated within the product. As such, it is considered to be inextricably bound, and not readily available for exposure. This product contains crystalline silica. As provided, and during normal use of this product, the crystalline silica is encapsulated within the product. As such, it is considered to be inextricably bound, and not readily available for exposure. Use of this product would not subject the user to the compliance requirements of 29CFR1910.1053 or 1926.1153.

Unlisted ingredients are not 'hazardous' per the Occupational Safety and Health Administration Hazard Communication Standard (29 CFR 1910.1200) and/or are not found on the Canadian Workplace Hazardous Materials Information System ingredient disclosure list. See Section 8 for exposure limit guidelines.

### **SECTION 4: FIRST AID MEASURES**

IF IN EYES: Use an eye wash to remove a chemical from your eye regardless of the level of hazard. Flush the affected eye for at least twenty minutes. Tilt the head to prevent chemical from transferring to the uncontaminated eye. Seek medical advice after flushing.

IF ON SKIN: Wash with soap and water. Remove contaminated clothing and launder. Get medical attention if irritation develops or persists.

IF INHALED: Remove to fresh air. Call a physician if symptoms persist.

IF SWALLOWED: Do not induce vomiting. Seek medical attention if symptoms develop. Provide medical care provider with this MSDS. Induced vomiting may lead to as piration of the material into the lungs potentially causing chemical pneumonitis that may be fatal.

# **SECTION 5: FIRE FIGHTING MEASURES**

EXTINGUISHING MEDIA: Use water spray, foam, dry chemical or carbon dioxide.

UNUSUAL FIRE AND EXPLOSION HAZARDS: There is a possibility of pressure buildup in closed containers

when heated. Water spray may be used to cool the containers. Persons exposed to products of combustion should wear self-

SPECIAL FIRE FIGHTING INSTRUCTIONS: Persons exposed to products of combustions hould wear self-

contained breathing apparatus and full protective equipment.

HAZARDOUS COMBUSTION PRODUCTS: Carbon dioxide, Carbon monoxide Chlorine containing gases

### SECTION 6: ACCIDENTAL RELEASE MEASURES

SPECIAL PROTECTION: Exposure to the spilled material may be irritating or harmful. Follow

personal protective equipment recommendations found in Section 8 of this MSDS. Additional precautions may be necessary based on special circumstances created by the spill including; the material spilled, the

quantity of the spill, the area in which the spill occurred.

METHODS FOR CLEAN-UP: Dike if necessary, contain spill with inert absorbent and transfer to

containers for disposal. Keep spilled product out of sewers, watersheds,

or water systems.

Transport Emergency Phone Number (CHEMTREC): 1-800-424-9300



FOSTER 30-80 802266PM

### SAFETY DATA SHEET

\_\_\_\_\_

### **SECTION 7: HANDLING AND STORAGE**

Handling: Avoid contacting and avoid breathing the material. Use only in a well ventilated

area.

Storage: Store in a cool, dry place. Protect from freezing. Consult the Technical Data Sheet for specific storage instructions.

### SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

### **EXPOSURE LIMITS:**

Chemical Name	Note	ACGIH EXPOSURE LIMITS	OSHA PEL
Titanium dioxide	* (see below)	10 mg/m3 TWA	15 mg/m3 TWA (total dust)
Crystalline silica	* (see below)	0.025 mg/m3 TWA (respirable particulate matter)	((250)/(%SiO2 + 5) mppcf TWA (respirable)); ((10)/(%SiO2 + 2) mg/m3 TWA (respirable)); ((30)/(%SiO2 + 2) mg/m3 TWA (total dust))

<sup>\*</sup>This product contains one or more materials that may be hazardous when present as an airborne dust. During normal handling of the product, the material is encapsulated within the product and will not present an exposure risk. Once the product has reached its final state and is abraded or disturbed, dusting and exposure may occur. This product contains titanium dioxide, which is hazardous when present as an airborne dust. As provided, and during normal use of this product, this substance is encapsulated within the product. As such, it is considered to be inextricably bound, and not readily available for exposure. This product contains crystalline silica. As provided, and during normal use of this product, the crystalline silica is encapsulated within the product. As such, it is considered to be inextricably bound, and not readily available for exposure. Use of this product would not subject the user to the compliance requirements of 29CFR1910.1053 or 1926.1153.

#### **ENGINEERING CONTROL METHODS:**

VENTILATION: General room ventilation might be required under normal conditions

of use.

EYE PROTECTION: Wear safety glasses when handling this product.

SKIN PROTECTION: Avoid skin contact by wearing chemically resistant gloves and long

sleeved shirt. An apron may be appropriate if splashing can occur.

GLOVES: Nitrile

RESPIRATORY PROTECTION: No respiratory protection required under normal conditions of use.

Respirators should be selected by and used following requirements

found in OSHA's respirator standard (29 CFR 1910.134).

### SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE: Liquid COLOR: White ODOR: Ammonia ODOR THRESHOLD: Not established Not established pH: FREEZING/MELTING POINT (deg. C): Not established BOILING POINT (deg. C): Not established Non flammable FLASH POINT: **EVAPORATION RATE:** Not established

FLAMMABILITY: Not a flammable solid or gas

UPPER EXPLOSIVE LIMIT (% in air):

Not established
LOWER EXPLOSIVE LIMIT (% in air):

Not established



FOSTER 30-80 802266PM

### SAFETY DATA SHEET

VAPOR PRESSURE (mm Hg): Not established VAPOR DENSITY: Not established

WEIGHT PER GALLON (lbs.): 11.60 SPECIFIC GRAVITY: 1.400

SOLUBILITY: Not established OCTANOL/WATER COEFFICIENT: Not established AUTOIGNITION TEMPERATURE: Not established DECOMPOSITION TEMPERATURE: Not established VISCOSITY: No data available.

SOLIDS (% by weight): 68.5 VOC, weight percent 1.50

VOC, U.S. EPA Method 24, less water and exempt 33g/liter of material

solvents (theoretically determined)

#### SECTION 10: STABILITY AND REACTIVITY

STABILITY: Stable under normal conditions.

CHEMICAL INCOMPATIBILITY: Not established HAZARDOUS POLYMERIZATION: Will not occur.

HAZARDOUS DECOMPOSITION PRODUCTS: Carbon monoxide, carbon dioxide Chlorine

containing gases

### SECTION 11: TOXICOLOGICAL INFORMATION

Component Toxicity / Toxicology Data:

COMPONENT NAME	LD50/LC50
Chlorinated paraffin	Oral LD50 Rat > 21,500 microliter/kg
Chlorinated paraffin	Oral LD50 Rat > 21,500 microliter/kg

## This product is a mixture. Unless noted, the information below is based on components.

Skin corrosion/irritation: No irritation hazard in normal industrial use.

Serious eye damage / irritation :No irritation hazard in normal industrial use.

Respiratory / skin sensitization: No data available.

Germ cell mutagenicity: No data available.

Carcinogenicity: Contains a material that may cause cancer.

Reproductive toxicity: No data available.

Specific target organ toxicity-single exposure: No data available.

Respiratory irritation / Narcotic effects: No data available.

Specific target organ toxicity-repeated exposure: No data available.

Target organs potentially affected by exposure: Kidneys Liver Lungs Skin

Aspiration hazard: Not an aspiration hazard.

Medical Conditions Aggravated by Exposure: Liver disease, Kidney disease, Lung disease, Skin disease including eczema and sensitization

## **SECTION 12: ECOLOGICAL INFORMATION**

OVERVIEW: No ecological information available for this product.



FOSTER 30-80 802266PM

#### SAFETY DATA SHEET

\_\_\_\_\_

MOBILITY: No data available. PERSISTENCE: No data available. BIOACCUMULATION: No data available.

### This product has not been tested for ecological effects. Relevant information for components is listed below:

Component:	Ecotoxicity values:
Chlorinated paraffin	Acute Toxicity (Fish): 96 Hr LC50 Oncorhynchus mykiss: >0.0109 mg/L [flow-through]; 96 Hr LC50 Oncorhynchus mykiss: 94.5 - 271 mg/L [static]; 96 Hr LC50
	Lepomis macrochirus: >0.1 mg/L [flow-through]
	Acute Toxicity (Daphnia): Not established
	Acute Toxicity (Algae): Not established
Chlorinated paraffin	Acute Toxicity (Fish): 96 Hr LC50 Oncorhynchus mykiss: >0.0109 mg/L [flow-through]; 96 Hr LC50 Oncorhynchus mykiss: 94.5 - 271 mg/L [static]; 96 Hr LC50
	Lepomis macrochirus: >0.1 mg/L [flow-through] Acute Toxicity (Daphnia): Not established
	Acute Toxicity (Algae): Not established

### **SECTION 13: DISPOSAL CONSIDERATIONS**

To the best of our knowledge, this product does not meet the definition of hazardous waste under the U.S. EPA Hazardous Waste Regulations 40 CFR 261. Solidify and dispose of in an approved landfill. Consult state, local or provincial authorities for more restrictive requirements.

# **SECTION 14: TRANSPORT INFORMATION**

Consult Bill of Lading for transportation information.

US DOT: NOT REGULATED

IATA: UN3077, ENVIRONMENTALLY HAZARDOUS SUBSTANCES, SOLID,

N.O.S. (C14-C17 CHLORINATED PARAFFIN), 9, III, MARINE

POLLUTANT. (PACKAGES <5 L, NOT REGULATED. SEE IATA 4.4,

SP A 197).

IMDG: UN3077, ENVIRONMENTALLY HAZARDOUS SUBSTANCES, SOLID,

N.O.S. (C14-C17 CHLORINATED PARAFFIN), 9, III, MARINE POLLUTANT (PACKAGES <5 L NOT REGULATED, IMDG 3.3, SP

969).

# **SECTION 15: REGULATORY INFORMATION**

**INVENTORY STATUS** 

U.S. EPA TSCA: This product is in compliance with the Toxic Substances Control Act's

Inventory requirements.

CANADIAN CEPA DSL: The components of this product are included on the DSL or are exempt

from DSL requirements.

EUROPEAN REACH: As a result of the introduction of REACH into Europe, this product

cannot be imported into Europe unless the REACH requirements are

met.

AUSTRALIA AICS: This product contains a component that is not on the Australian

Inventory (AICS).

If you need more information about the inventory status of this product call 651-236-5858.

This product may contain chemical substances that are regulated for export by various government agencies (such as the Environmental Protection Agency, the Bureau of Industry and Security, or the Drug Enforcement Administration, among others). Before exporting this product from the USA or Canada, we recommend you contact us at reg\_request@hbfuller.com to request an export review.

FOSTER 30-80 802266PM

### SAFETY DATA SHEET

This product contains a chemical substance that is subject to a Significant New Use Rule (SNUR) under Section 5(a)(2) of TSCA:

.alpha.-(4-Nonylphenyl)-.omega.-hydroxypoly(oxy-1,2-ethanediyl)
.alpha.-(Nonylphenyl)-.omega.-hydroxypoly(oxy-1,2-ethanediyl)
4-Nonylphenol, branched

79 FR 59186, Oct 1, 2014 (proposed rule) 79 FR 59186, Oct 1, 2014 (proposed rule, listed under .alpha.-(Nonylphenyl)-.omega.-hydroxy-poly(oxy-1,2-ethanediyl))

# FEDERAL REPORTING

\*This product contains one or more materials that may be hazardous when present as an airborne dust. During normal handling of the product, the material is encapsulated within the product and will not present an exposure risk. Once the product has reached its final state and is abraded or disturbed, dusting and exposure may occur. This product contains titanium dioxide, which is hazardous when present as an airborne dust. As provided, and during normal use of this product, this substance is encapsulated within the product. As such, it is considered to be inextricably bound, and not readily available for exposure. This product contains crystalline silica. As provided, and during normal use of this product, the crystalline silica is encapsulated within the product. As such, it is considered to be inextricably bound, and not readily available for exposure. Use of this product would not subject the user to the compliance requirements of 29CFR1910.1053 or 1926.1153.

#### EPA SARA Title III Section 313

Unless listed below, this product does not contain toxic chemical(s) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA) and 40 CFR part 372. EPA has advised that when a percentage range is listed the midpoint may be used to fulfill reporting obligations.

Chemical Name	CAS#	%

### **STATEREPORTING**

Proposition 65, The Safe Drinking Water and Toxic Enforcement Act of 1986:

Unless listed below, this product does not contain known levels of any chemical known to the State of California to cause cancer or reproductive harm.

Chemical Name/List		CAS	Percent
Titanium dioxide	(Carcinogen)	13463-67-7	1 - 5
Quartz	(Carcinogen)	14808-60-7	0.1 - 1
Styrene	(Carcinogen)	100-42-5	0.1 - 1
Cumene	(Carcinogen)	98-82-8	0.1 - 1
Naphthalene	(Carcinogen)	91-20-3	0.001 - 0.01
ethylbenzene	(Carcinogen)	100-41-4	0.001 - 0.01
Diethanolamine	(Carcinogen)	111-42-2	< 10 ppm
Benzene	(Carcinogen)	71-43-2	< 10 ppm
Ethylene glycol	(Developmental toxin)	107-21-1	0.1 - 1
Benzene	(Developmental toxin)	71-43-2	< 10 ppm
Benzene	(Male reproductive toxin)	71-43-2	< 10 ppm

# **Substances of Very High Concern (SVHC) Content:**

Unless listed below, this product does not contain SVHC's at 0.1% or greater, as of the version date of this SDS.

- 4-Nonylphenol, ethoxylated
- 4-Nonylphenol, ethoxylated





#### SAFETY DATA SHEET

\_\_\_\_\_

### **SECTION 16: OTHER INFORMATION**

SDS VERSION DATE: 02-11-2020

This Safety Data Sheet is prepared to comply with the United States Occupational Safety and Health Administration (OSHA) Hazard Communication Standard (29 CFR 1910.1200) and the Canadian Workplace Hazardous Materials Information System (WHMIS).

HMIS RATING: HEALTH -- 2 FLAMMABILITY -- 0 REACTIVITY -- 0

See SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for personal protective equipment recommendations.

Prepared by: The Global Regulatory Department

Phone: 651-236-5842

The information and recommendations set forth herein are believed to be accurate. Because some of the information is derived from information provided to H.B. Fuller Construction Products, Inc. from its suppliers, and because H.B. Fuller Construction Products, Inc. has no control over the conditions of handling and use, H.B. Fuller Construction Products, Inc. makes no warranty, expressed or implied, regarding the accuracy of the data or the results to be obtained from the use thereof. The information is supplied solely for your information and consideration, and H.B. Fuller Construction Products, Inc. assumes no responsibility for use or reliance thereon. It is the responsibility of the user of H.B. Fuller Construction Products, Inc. products to comply with all applicable federal, state and local laws and regulations.