# **Safety Data Sheet**

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: March 27, 2018 Revision: March 27, 2018

#### 1 Identification

· Product identifier

· Trade name: Eco-Hanger Grip Adhesive Zero VOC

· Article number: 22-15 ZERO

· Recommended use and restriction on use

· Recommended use: Adhesive.

· Restrictions on use: No relevant information available.

Details of the supplier of the Safety Data Sheet

· Manufacturer/Supplier:

Mon-Eco Industries, Inc.

5 Joanna Ct.

East Brunswick, NJ 08816 Phone: 732-257-7942

· Emergency telephone number:

ChemTel Inc.

(800)255-3924 (North America) +1 (813)248-0585 (International)



### 2 Hazard(s) identification

· Classification of the substance or mixture

Flam. Liq. 2 H225 Highly flammable liquid and vapor.

Eye Irrit. 2A H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

- Label elements
- · GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

Hazard pictograms:





**GHS02 GHS07** 

- · Signal word: Danger
- Hazard statements:

H225 Highly flammable liquid and vapor.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

· Precautionary statements:

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P233 Keep container tightly closed.

P240 Ground/bond container and receiving equipment.

P241 Use explosion-proof electrical/ventilating/lighting/equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P261 Avoid breathing mist, vapors, or spray.

P264 Wash thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

(Cont'd. on page 2)

Page: 2/11

(Cont'd. of page 1)

# **Safety Data Sheet**

### acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: March 27, 2018 Revision: March 27, 2018

Trade name: Eco-Hanger Grip Adhesive Zero VOC

P280 Wear protective gloves and eye protection.

P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with

water/shower.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P312 Call a poison center/doctor if you feel unwell.

P337+P313 If eye irritation persists: Get medical advice/attention.

P370+P378 In case of fire: Use foam, powder, or carbon dioxide for extinction.

P403+P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

Other hazards There are no other hazards not otherwise classified that have been identified.

## 3 Composition/information on ingredients

· Chemical characterization: Mixtures

	· Components:				
	79-20-9	methyl acetate	<ul><li>♠ Flam. Liq. 2, H225</li><li>♠ Eye Irrit. 2A, H319; STOT SE 3, H336</li></ul>	40-60%	
	1332-58-7	Clay		10-20%	
Ī	1317-65-3	limestone		5-10%	

#### Additional information:

For the listed ingredient(s), the identity and/or exact percentage(s) are being withheld as a trade secret. For the wording of the listed Hazard Statements, refer to section 16.

#### 4 First-aid measures

#### Description of first aid measures

#### After inhalation:

Supply fresh air: consult doctor in case of complaints.

Provide oxygen treatment if affected person has difficulty breathing.

#### · After skin contact:

Immediately remove any clothing soiled by the product.

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

#### · After eye contact:

Remove contact lenses if worn.

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

#### · After swallowing:

Rinse out mouth and then drink plenty of water.

Do not induce vomiting; immediately call for medical help.

### · Most important symptoms and effects, both acute and delayed:

Headache

Cramp

Dizziness

(Cont'd. on page 3)

Page: 3/11

# **Safety Data Sheet**

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: March 27, 2018 Revision: March 27, 2018

Trade name: Eco-Hanger Grip Adhesive Zero VOC

(Cont'd. of page 2)

Coughing

Breathing difficulty

Causes eye irritation.

Slight irritant effect on skin and mucous membranes.

Gastric or intestinal disorders when ingested.

Nausea in case of ingestion.

- · Danger: Vapours may cause drowsiness and dizziness.
- Indication of any immediate medical attention and special treatment needed: Treat symptomatically.

## 5 Fire-fighting measures

- · Extinguishing media
- Suitable extinguishing agents:

Foam

Fire-extinguishing powder

Gaseous extinguishing agents

Carbon dioxide

Water fog / haze

- · For safety reasons unsuitable extinguishing agents: Water spray
- Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

- Advice for firefighters
- · Protective equipment:

Wear self-contained respiratory protective device.

Wear fully protective suit.

Additional information:

Eliminate all ignition sources if safe to do so.

Cool endangered containers with water fog.

#### 6 Accidental release measures

### · Personal precautions, protective equipment and emergency procedures

Use respiratory protective device against the effects of fumes/dust/aerosol.

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation.

Keep away from ignition sources.

Protect from heat.

- · Environmental precautions Avoid release to the environment.
- · Methods and material for containment and cleaning up

Absorb with non-combustible liquid-binding material (sand, diatomite, acid binders, universal binders). Send for recovery or disposal in suitable receptacles.

Used rags or other cleaning materials should be soaked with water and placed in a sealed container.

Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

Page: 4/11

# **Safety Data Sheet**

#### acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: March 27, 2018 Revision: March 27, 2018

Trade name: Eco-Hanger Grip Adhesive Zero VOC

(Cont'd. of page 3)

### 7 Handling and storage

#### Handling

### Precautions for safe handling:

Handle with care.

Keep out of reach of children.

Avoid breathing mist, vapors, or spray.

Avoid contact with the eyes and skin.

Avoid splashes or spray in enclosed areas.

Use only in well ventilated areas.

Rags, metal wools / cuttings / shavings and waste papers soaked with product must be placed in a sealed metal container rated for flammable waste.

### Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Fumes can combine with air to form an explosive mixture.

Flammable gas-air mixtures may be formed in empty containers/receptacles.

#### Conditions for safe storage, including any incompatibilities

### Requirements to be met by storerooms and receptacles:

Avoid storage near extreme heat, ignition sources or open flame.

Store in cool, dry conditions in well sealed receptacles.

## Information about storage in one common storage facility:

Store away from foodstuffs.

Store away from oxidizing agents.

· Specific end use(s) No relevant information available.

### 8 Exposure controls/personal protection

#### · Control parameters

Control parameters				
· Components w	vith limit values that require monitoring at the workplace:			
79-20-9 methyl acetate				
PEL (USA)	Long-term value: 610 mg/m³, 200 ppm			
REL (USA)	Short-term value: 760 mg/m³, 250 ppm Long-term value: 610 mg/m³, 200 ppm			
TLV (USA)	Short-term value: 757 mg/m³, 250 ppm Long-term value: 606 mg/m³, 200 ppm			
EL (Canada)	Short-term value: 250 ppm Long-term value: 200 ppm			
EV (Canada)	Short-term value: 755 mg/m³, 250 ppm Long-term value: 605 mg/m³, 200 ppm			
LMPE (Mexico)	Short-term value: 250 ppm Long-term value: 200 ppm			
1332-58-7 Clay				
PEL (USA)	Long-term value: 15* 5** mg/m³ *total dust **respirable fraction			
REL (USA)	Long-term value: 10* 5** mg/m³			
	•	(Cont'd. on page 5)		

Page: 5/11

# **Safety Data Sheet**

### acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: March 27, 2018 Revision: March 27, 2018

Trade name: Eco-Hanger Grip Adhesive Zero VOC

		(Cont'd. of page 4)
	*total dust **respirable fraction	(======================================
TLV (USA)	Long-term value: 2* mg/m³ E; as respirable fraction	
EL (Canada)	Long-term value: 2 mg/m³	
EV (Canada)	Long-term value: 2(D) mg/m³ respirable	
LMPE (Mexico)	Long-term value: 2* mg/m³ A4, *fracción respirable	
1317-65-3 limestone		
PEL (USA)	Long-term value: 15* 5** mg/m³ *total dust **respirable fraction	
REL (USA)	Long-term value: 10* 5** mg/m³ *total dust **respirable fraction	
TLV (USA)	TLV withdrawn	

#### Exposure controls

### · General protective and hygienic measures:

The usual precautionary measures for handling chemicals should be followed.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes.

Avoid close or long term contact with the skin.

- · Engineering controls: No relevant information available.
- · Breathing equipment:

Wear appropriate NIOSH respirator when ventilation is inadequate and occupational exposure limits are exceeded.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· Eye protection:



Safety glasses

- · Body protection: Protective work clothing
- · Limitation and supervision of exposure into the environment

No relevant information available.

· Risk management measures No relevant information available.

## 9 Physical and chemical properties

Information on basic physical and chemical properties

(Cont'd. on page 6)

Page: 6/11

## **Safety Data Sheet**

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: March 27, 2018 Revision: March 27, 2018

Trade name: Eco-Hanger Grip Adhesive Zero VOC

	(Cont'd. of page
Appearance:	
Form:	Paste
Color:	Tan.
Odor:	Mild
Odor threshold:	Not determined.
pH-value:	Not determined.
Melting point/Melting range:	Not determined.
Boiling point/Boiling range:	>35 °C (>95 °F)
Flash point:	<-13 °C (<8.6 °F)
Flammability (solid, gaseous):	Not applicable.
Auto-ignition temperature:	Not determined.
Decomposition temperature:	Not determined.
Danger of explosion:	Product is not explosive. However, formation of explosive a vapor mixtures are possible.
Explosion limits	
Lower:	Not determined.
Upper:	Not determined.
Vapor pressure:	Not determined.
Density:	
Relative density:	1.12
Vapor density:	Not determined.
Evaporation rate:	Not determined.
Solubility in / Miscibility with	
Water:	Not miscible or difficult to mix.
Partition coefficient (n-octanol/wat	ter): Not determined.
Viscosity	
Dynamic:	Not determined.
Kinematic:	Not determined.
Other information	No relevant information available.

## 10 Stability and reactivity

- · Reactivity: No relevant information available.
- Chemical stability:
- Thermal decomposition / conditions to be avoided: Keep away from heat and direct sunlight.
- Possibility of hazardous reactions

Highly flammable liquid and vapor.

Reacts with strong alkali.

Reacts with strong acids and oxidizing agents.

Used empty containers may contain product gases which form explosive mixtures with air.

Can form explosive mixtures in air if heated above flash point and/or when sprayed or atomized.

Toxic fumes may be released if heated above the decomposition point.

(Cont'd. on page 7)

Page: 7/11

# **Safety Data Sheet**

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: March 27, 2018 Revision: March 27, 2018

Trade name: Eco-Hanger Grip Adhesive Zero VOC

(Cont'd. of page 6)

- · Conditions to avoid Excessive heat.
- · Incompatible materials Oxidizers, strong bases, strong acids
- · Hazardous decomposition products

Carbon monoxide and carbon dioxide

Hydrocarbons

### 11 Toxicological information

- Information on toxicological effects
- · Acute toxicity: Based on available data, the classification criteria are not met.
- · LD/LC50 values that are relevant for classification: None.
- · Primary irritant effect:
- · On the skin: Slight irritant effect on skin and mucous membranes.
- · On the eye: Irritating effect.
- · Sensitization: No sensitizing effects known.
- · IARC (International Agency for Research on Cancer):

None of the ingredients are listed.

· NTP (National Toxicology Program):

None of the ingredients are listed.

· OSHA-Ca (Occupational Safety & Health Administration):

None of the ingredients are listed.

· Probable route(s) of exposure:

Ingestion.

Inhalation.

Eve contact.

Skin contact.

- · Germ cell mutagenicity: Based on available data, the classification criteria are not met.
- · Carcinogenicity: Based on available data, the classification criteria are not met.
- · Reproductive toxicity: Based on available data, the classification criteria are not met.
- · STOT-single exposure: May cause drowsiness or dizziness.
- · STOT-repeated exposure: Based on available data, the classification criteria are not met.
- · Aspiration hazard: Based on available data, the classification criteria are not met.

# 12 Ecological information

- · Toxicity
- · Aquatic toxicity No relevant information available.
- · Persistence and degradability No relevant information available.
- · Bioaccumulative potential: No relevant information available.
- · Mobility in soil: No relevant information available.
- Additional ecological information
- · General notes: Avoid release to the environment.
- Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

(Cont'd. on page 8)

Page: 8/11

# **Safety Data Sheet**

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: March 27, 2018 Revision: March 27, 2018

Trade name: Eco-Hanger Grip Adhesive Zero VOC

(Cont'd. of page 7)

(Cont'd. on page 9)

• Other adverse effects No relevant information available.

### 13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Can be disposed of with household garbage after solidification following consultation with the waste disposal facility operator and the pertinent authorities and adhering to the necessary technical regulations. The user of this material has the responsibility to dispose of unused material, residues and containers in compliance with all relevant local, state and federal laws and regulations regarding treatment, storage and disposal for hazardous and nonhazardous wastes.

- **Uncleaned packagings**
- · Recommendation: Disposal must be made according to official regulations.

14 Transport information		
· UN-Number · DOT, ADR, IMDG, IATA	UN1133	
UN proper shipping name DOT, IATA ADR, IMDG	Adhesives ADHESIVES	
· Transport hazard class(es) · DOT		
· Class · Label	3 Flammable liquids 3	
ADR		
· Class · Label	3 (F1) Flammable liquids 3	
· IMDG, IATA		
· Class · Label	3 Flammable liquids 3	

Page: 9/11

# **Safety Data Sheet**

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: March 27, 2018 Revision: March 27, 2018

Trade name: Eco-Hanger Grip Adhesive Zero VOC

(Cont'd. of page 8) · Packing group · DOT, ADR, IMDG, IATA Ш · Environmental hazards · Marine pollutant: No Special precautions for user Warning: Flammable liquids Danger code (Kemler): · EMS Number: F-E,S-D Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable. Transport/Additional information: DOT Limited Quantity for packages less than 30 kg gross and inner packagings less than 5 L each. **ADR** Limited Quantity for packages less than 30 kg gross and inner packagings less than 5 L each. · IMDG Limited Quantity for packages less than 30 kg gross and inner packagings less than 5 L each. ·IATA Limited Quantity for packages less than 30 kg gross and inner packagings less than 0.5 L each

## 15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- · United States (USA)
- ·SARA
- Section 302 (extremely hazardous substances):

None of the ingredients are listed.

· Section 355 (extremely hazardous substances):

None of the ingredients are listed.

· Section 313 (Specific toxic chemical listings):

(Cont'd. on page 10)

Page: 10/11

## **Safety Data Sheet**

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: March 27, 2018 Revision: March 27, 2018

Trade name: Eco-Hanger Grip Adhesive Zero VOC

(Cont'd. of page 9)

None of the ingredients are listed.

· TSCA (Toxic Substances Control Act)

All ingredients are listed.

· Proposition 65 (California)

· Chemicals known to cause cancer:

None of the ingredients are listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients are listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients are listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients are listed.

· EPA (Environmental Protection Agency):

None of the ingredients are listed.

IARC (International Agency for Research on Cancer):

None of the ingredients are listed.

NIOSH-Ca (National Institute for Occupational Safety and Health):

None of the ingredients are listed.

· Canadian Domestic Substances List (DSL):

All ingredients are listed.

### 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Date of preparation / last revision March 27, 2018 / -

· Abbreviations and acronyms:

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistant, Bio-accumulable, Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety and Health

OSHA: Occupational Safety & Health Administration

Flam. Liq. 2: Flammable liquids – Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A

STOT SE 3: Specific target organ toxicity (single exposure) - Category 3

· Sources

Website, European Chemicals Agency (echa.europa.eu)

Website, US EPA Substance Registry Services (ofmpub.epa.gov/sor internet/registry/substreg/home/overview/home.do)

Website, Chemical Abstracts Registry, American Chemical Society (www.cas.org)

Patty's Industrial Hygiene, 6th ed., Rose, Vernon, ed. ISBN: 978-0-470-07488-6

(Cont'd. on page 11)

Page: 11/11

# **Safety Data Sheet**

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: March 27, 2018 Revision: March 27, 2018

Trade name: Eco-Hanger Grip Adhesive Zero VOC

(Cont'd. of page 10)

Casarett and Doull's Toxicology: The Basic Science of Poisons, 8th Ed., Klaasen, Curtis D., ed., ISBN: 978-0-07-176923-5.

Safety Data Sheets, Individual Manufacturers

SDS Prepared by: ChemTel Inc. 1305 North Florida Avenue Tampa, Florida USA 33602-2902

Toll Free North America 1-888-255-3924 Intl. +01 813-248-0573

Website: www.chemtelinc.com